



Suitable for:

Metal panels / Metal mesh Gypsum board / Mineral fiber




10 Kg/m² Maximum bearing load



Easy Fox™

- Easy to install
- · Overlap model
- Fast and safety



reg: VE2009U000007

TWI


TWISTER | the quicker way to hang T-Grid



 Double hangers with adjustable springs

THE BOX CONTAINS*:

- 5 pcs 2135mm Main T
- 16 pcs 1220mm Cross T
- 16 pcs 610mm Cross T



ESTIMATING GUIDE:

Room	2,6 m	3,6 m	4,6 m	5,6 m	6,6 m	7,6 m	8,6 m
2,8 m	1 kit	1 kit	2 kit	2 kit	2 kit	3 kit	3 kit
3,8 m	1 kit	2 kit	2 kit	3 kit	3 kit	3 kit	4 kit
4,8 m	2 kit	2 kit	3 kit	3 kit	4 kit	4 kit	5 kit
5,8 m	2 kit	3 kit	3 kit	4 kit	4 kit	5 kit	5 kit
6,8 m	2 kit	3 kit	4 kit	4 kit	5 kit	6 kit	6 kit
7,8 m	2 kit	3 kit	4 kit	5 kit	6 kit	6 kit	7 kit
8,8 m	3 kit	4 kit	4 kit	5 kit	6 kit	7 kit	8 kit

Metal Ceiling Easy Fox™ modules for 10m²

*Wall angles, fastening and screws are not included in the box

TECHNICAL AND ENVIRONMENTAL PERFORMANCES

APPLICATION	Indoor application UNI EN ISO 13964				
EXPOSURE CLASS	A Class				
FLEXION RESISTANCE	Maximum span mm 1200 - 1 Class EN13964				
CORROSION RESISTANCE	Galvanized steel products: C2 Class Pre-painted galvanized steel products: C3 Class				
(RH%) RELATIVE HUMIDITY RESISTANCE	Galvanized steel products: ≤ 90% Pre/post-painted galvanized steel products: > 90%				
FIRE REACTION	A1 Class UNI EN 13501-1				
MAXIMUM LOAD	10 Kg/m²				
LIGHT REFLECTION	Gloss smooth white: up to 85% Iso 7724-2 (3)				
COLOR STABILITY	In compliance with stadard technical tolerances. Test according the ΔE - CIELab method. Iso 7724-2 (3)				
CLEANING	Wet cloth with warm water and neutral non-abrasive detergents.				
DURABILITY OF OF PAINTED ITEMS	C Class EN13964				
DURABILITY OF OF GALVANIZED ITEMS	B Class EN13964				
RELEASE OF DANGEROUS SUBSTANCES*	None CAM 2.4.1.3 EN13964				
DISASSEMBLY*	100% recyclable CAM .4.1.1				
RECYCLE PRODUCT CONTENT*	32,8% CAM 2.4.1.8 compliance				
MATERIAL DEMOLITION AND REMOVAL*	Non hazardous waste in compliance with CAM 2.5.1.				
FORMALDEHYDE*	E1 Class CAM 2.3.5.5				
GREEN BUILDING*	EPD LEED (BREEAM and ITACA for cross-section aspects)				

^{*} Data declaration as required by the ISO 14021 | 14025 | EN 15804 - EPD



MADE IN ITALY MANUFACTURING QUALITY • DESIGN I.F.C. LTD 14, Habana'im St. P.Box 12384 - Ashdod - Israel Office +972-35332108 Fax +972-35331778 info@ifc.co.il ifc.co.il



